

*Corrugated Switchboard Runner V-groove non-conductive surface insulates worker to prevent shock!*


- Every roll is proof tested at the specified voltage, over the entire surface of the matting to ensure best protection
- Ideal for industrial environment
- As a non-conductive mat, Corrugated Switchboard Runner brings safety and security to a higher degree

**CORRUGATED SWITCHBOARD APPLICATIONS**

Provides a heavy duty solution for dry areas e.g.: Computer workstation, Fuse box, Control panel and Switchboard.

**FEATURES**

- Dielectric rating: 30,000 volts
- Meets ASTM standards: D178, Type 2, Class 2
- Meets all optional ASTM standards for resistance to ozone, flames and oils



**BLACK**

AVAILABILITY		TECHNICAL DATA	PROFILE
<b>STANDARD SIZES</b>	<b>ROLLS</b>	Weight: .64lbs per sq. ft. Material: Extruded vinyl Surface: Corrugated Tensile strength: 700 PSI meets ASTM-D-412 Flammability: Meets ASTM-D-1962 Oil resistance: Meets ASTM-D-471	 <b>Thickness: 1/4"</b>
<b>Unavailable</b>	<b>3' X 75'</b>		
<b>CUSTOM SIZES</b>	<b>WARRANTY</b>		
<b>Length cuts up to 75'</b>	<b>Standard limited one year</b>		
<b>USE AND CARE</b>			
<b>Vacuum</b>			

AUTHORIZED DISTRIBUTOR



T: 1 800 628 5463  
 F: 419 332 4180  
[www.crown-mats.com](http://www.crown-mats.com)

Products and their related details are subject to change. Please contact our Customer Service department to obtain current information.